



SUNDT

# HEAVY EQUIPMENT PRECAUTIONS

Project teams should minimize exposure to COVID-19 on heavy equipment by:

*Disinfecting and sanitizing  
high-contact surfaces*

*Limiting equipment  
and operator rotation*

## DISINFECTING AND SANITIZING HIGH CONTACT SURFACES

---

The equipment operator should disinfect and sanitize each high contact surface at the beginning and end of each shift:

- Wear gloves while disinfecting and sanitizing.
- Clean high contact surfaces (i.e. steering wheels, grab handles, door handles, joysticks, switches, seatbelts, seats, armrests, consoles, instrument clusters and gear selectors).
- Be aware of any sensitive electronics in the cab so that liquid cleaners are not applied directly to them.
- Ensure the cab is well ventilated by opening windows and doors. Where possible, leave the cab ventilated in between operators.

## LIMITING EQUIPMENT OPERATOR ROTATION

---

Where possible, limit the number of operators rotating onto a specific piece of equipment. This means having one operator run one specific piece of equipment during the rotation rather than having multiple operators run a single machine.

## TRACKING

---

Sites should track which operators operate a specific machine so that if there is a positive COVID-19 test, the sites can direct cleaning efforts as well as limit the number of potentially exposed employees.

---

FOR ANY QUESTIONS ABOUT SUNDT'S COVID-19 POLICIES EMAIL [CRISIS@SUNDT.COM](mailto:CRISIS@SUNDT.COM) OR CALL 480.293.3255

---